



Product Name:

Diesel PD 5W-40

Comma recommends this product for applications requiring:

VW 505 01; FORD WSS M2C917-A; VW 502 00, VW 505 00; BMW LL-04; MB 229.31

ACEA C3; API SM CF

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine. Also suitable for Petrol & Diesel vehicles fitted with exhaust after-treatment units that require an ACEA C3 grade.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at www.CommaOil.com

Typical Inspection Data:

Specific gravity at 20°C	0.850
Viscosity @ 100°C	13.0 cSt
Viscosity @ 40°C	75 cSt
Viscosity Index	160
Viscosity CCS @ -30°C	6400 cP
T.B.N.	7.2 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the day of the year, the last two figures the year.