

TECHNICAL CHARACTERISTICS

SELENIA GOLD SYNTH

PRODUCT CODE: 1201

APPLICATION

Lubricant designed to satisfy all the requirements of both petrol and diesel passenger car engines. The special synthetic based formula ensures total engine protection and high efficiency at all running temperatures.

SPECIFICATIONS

SAE 10W-40, ACEA A3/B3, API SL/CF, VW 500.00 - 505.00

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUES
APPEARANCE	--	--	B. & C.
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,872
VISCOSITY @ 100°C	ASTM D 445	cSt	14,5
VISCOSITY INDEX	ASTM D 2270	--	148
FLASH POINT Cl. O. C.	ASTM D 92	°C	220
T.B.N.	ASTM D 2896	mg KOH/g	7,4
POUR POINT	ASTM D 97	°C	-30
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

RESEARCH & DEVELOPMENT

05/2004

All technical data is provided for reference only.

FL SELENIA s.p.a.

Sede Legale:
Via Santena, 1
10029 Villastellone (Torino)
Tel. +39 011.96131
Fax +39 011.9613555

Cap. Soc. €2.000.000 i.v.
Partita IVA 00844490151
Cod. Fisc. 00844490151
Reg. Imp. Torino 00844490151
www.flselenia.com