

Mobil Super 3000 X1 5W-40

Premium Fully Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 3000 range of lubricants are ultra premium synthetic engine oils, designed to provide outstanding levels of protection and performance

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 3000 X1 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend Mobil Super 3000 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 3000 X1 meets or exceeds the following 5W-40 industry and builder specifications:

API SM/SL/SJ/CF	X
ACEA A3/B3	X
A3/B4	X



Mobil Super 3000 X1 has the following builder approvals:	5W-40
BMW Longlife Oil 98	X
OPEL Diesel Service Fill GM-LL-B-025	X
Special Oil List	X
MB-Approval 229.3	X
VW 505 00	X
VW 502 00	X

Typical Properties

Mobil Super 3000 X1	5W-40
Viscosity, ASTM D 445	
cSt @ 40° C	83.2
cSt @ 100° C	14.1
Sulfated Ash, wt%, ASTM D 874	1.0
Phosphorous	0.09
Flash Point, °C, ASTM D 92	220
Density @15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-39

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment

The Mobil logotype, the Pegasus design, and Mobil 1 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.